

Philips
Coaxial cable

1,5 m

F-Type Black

SWV2842W



Ensure a reliable connection

with this satellite coaxial cable

Depend on this satellite coaxial cable for transferring audio/video signals between your components.

Enjoy good picture quality

- Crafted with quality construction
- Nickel-plated connectors for reliable contact

Enjoy good audio quality

- High purity copper conductor for reliable signal transfer

Easy installation

- Non-slip ergonomic grip for easy use

Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS
sense and simplicity

Coaxial cable
1,5 m F-Type Black

Specifications

Packaging dimensions

- **Packaging dimensions (W x H x D):**
9.4 x 23.6 x 3.6 cm
- **Nett weight:** 0.080 kg
- **Gross weight:** 0.100 kg
- **Tare weight:** 0.020 kg
- **EAN:** 87 12581 38097 7
- **Number of products included:** 1
- **Packaging type:** Blister

Outer Carton

- **Outer carton (L x W x H):** 33.0 x 25.7 x 17.8 cm
- **Nett weight:** 0.960 kg

- **Gross weight:** 1.500 kg
- **Tare weight:** 0.540 kg
- **EAN:** 87 12581 38099 1
- **Number of consumer packagings:** 12

Inner Carton

- **Inner carton (L x W x H):** 24.4 x 10.4 x 15.7 cm
- **Nett weight:** 0.320 kg
- **Gross weight:** 0.500 kg
- **Tare weight:** 0.180 kg
- **EAN:** 87 12581 38098 4
- **Number of consumer packagings:** 4

SWV2842W/I0

Product highlights

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Quality construction

Quality construction uses only top grade materials to create products of extended durability.

Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

Nickel-plated connectors

Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.



Issue date 2008-10-28

Version: 1.1.7

12 NC: 8670 000 35488
EAN: 87 12581 38097 7

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com